

Air-Powered Standard Drive



BULK, SAUSAGE-PACK and MINI-COAXIAL CARTRIDGES



200-5



100-9

Easy to assemble and clean

MODEL	FEATURES	CAPACITY	CHAMBER	WT (lb)
BULK and SAUSAGE-PACK				
100-12*	Lowest volume, bulk load. Holds 10 oz sausage-pack.	10 oz	2"D x 8½"L	3.25
100-9*	Popular, general purpose model. Bulk load. Holds 10 or 20 oz sausage-pack.	1½ pint, 20 oz	2"D x 14"L	4.75
100-10*	Increased capacity minimizes reloading.	1 quart	2"D x 18"L	5.75
100-18	Popular 10 or 20 oz sausage-pack model. Teflon Packings. Bulk-capable with no change of parts.	1½ pint, 20 oz	2"D x 14"L	4.75
200-5**	JUMBO diameter, for bulk only. High volume, any viscosity.	2½ quart	3¾"D x 16"L	7.75
SAUSAGE-PACK and MINI-COAXIAL CARTRIDGE				
100-13***	With Hytrel packing and poly-finger piston for 10 or 20 oz sausage packs.	20 oz	2"D x 14"L	4.75
100-14***	With Hytrel packing and poly-finger piston for 10 oz sausage-pack or mini-coaxial cartridges.	10 oz	2"D x 10"L	3.75
100-19	For 3M Loop Sealant and 3M Nozzle.	1 Liter	2"D x 25"L	7.5

* supplied with 32-55 nozzle.
 ** supplied with 32-35 nozzle.
 *** supplied with three 235-3 plastic cones.

Air pressure regulators can be supplied as an extra.
 All models accept ½"NPT male air-line fittings.

Albion Standard Air-Powered Drive models require minimum physical effort. Designed and built for repetitive work, they provide perfect even flow without interruption.

FEATURES:

- ✓Dispenses most viscous materials at high speed and in large volume
- ✓3-way air valve for instant pressure release
- ✓Full porting to prevent piston upset
- ✓Dent-resistant steel barrel
- ✓Scratch and rust-resistant plated finish
- ✓All parts are replaceable and in stock

BACKED BY ALBION'S WARRANTY AND COMMITMENT TO PROFESSIONAL QUALITY TOOLS

CARTRIDGE MODELS



365-2



360-1

POSITIVE AIR SEAL

MODEL	CARTRIDGE	CAPACITY	CHAMBER	WT (lb)
360-1	Standard 8½". Supplied with 2-G16 ring cap, 26-28 front cap, and 32-55 nozzle	¼ gallon	2"D x 8½"L	3
365-2	Spouted quart	1 quart	2½"D x 12"L	5
365-3	Unspouted quart. Supplied with 220-G01 front cap and 32-55 nozzle	1 quart	2½"D x 12"L	5.5

Air pressure regulators can be supplied as an extra.
 All models accept ½"NPT male air-line fittings.

If air contamination of sealant is a concern, consider Albion's patented DOUBLE-ACTION Air Models. CATALOG ON REQUEST

Check our Web Site for new items!



ALBION Engineering Co.
 1250 N. Church Street
 Moorestown, NJ 08057-1102
 856-235-6688

www.albioneng.com

FAX TOLL-FREE: 800-841-7132
 (USA, Canada, Puerto Rico & US Virgin Islands)

INTERNATIONAL FAX: 001-856-235-9460
E-MAIL: service@albioneng.com

Catalog
260C

INDUSTRIAL STYLE



Full-barrel provides extra support for the most viscous materials.

467- Air-Powered Drive
shown with Full-Barrel, optional 383 Series Cartridge and Nozzle

Compact. Lightweight carriageless units produce less wrist strain.



467-1 Metal Bezel

Recommended for both Factory or Field use

Designed for use with Industrial Style 383-250 Cartridge Assemblies

Originally designed for the Aircraft and Electronics industries, Albion's "compact" Industrial Models provide easy application of small amounts of material to hard-to-reach areas, without obstructing view of nozzle tip.


Using 383-250 Series Cartridge Assemblies, these tools are ideal for dispensing low-viscosity epoxies, sophisticated resins, Sem-Kits® and other reactive materials.

Available with metal or plastic bezel rings or full-barrel retainers for extra support with the most viscous materials.

MODEL	RETAINER	CAPACITY	WT (lb)
467-1	Metal Bezel Ring	2½ thru 12 oz	2
467-2	Plastic Bezel Ring	2½ thru 12 oz	2
467-3	Full-Barrel	2½ oz	2.25
467-4	Full-Barrel	6 oz	2.25
467-5	Full-Barrel	8 oz	2.5
467-6	Full-Barrel	12 oz	2.5

See Albion's "Cartridges & Cartridge Accessories" Catalog for Industrial Style Series 383-250 Cartridges

AIR-POWER ACCESSORIES



251-4 Air Compressor



138-6 1/8" NPT Pipe Coupling



138-7 1/4" to 1/8" NPT Thread Reducer



363-2 Quick Disconnect Coupling with 1/4" NPT Thread



137-2 Air Pressure Regulator with 1/4" NPT Thread



138-9 1/4" NPT Tee Connection



137-3 Air Pressure Gauge



193-4 1/4" NPT Close Pipe Nipple



193-5 1/4" NPT x 2 1/2" Pipe Nipple



Compressor Kits Connect your compressor with 1/4" NPT thread.



KIT 444-1 FOR SINGLE GUN Quick Coupling



KIT 444-2 FOR TWO GUN Quick Coupling



KIT 444-3 FOR SINGLE GUN Regulator, Gauge and Coupling Without Gauge Kit No. 444-5



KIT 444-4 FOR TWO GUN Regulator, Gauge and Coupling Without Gauge Kit No. 444-6



Kits for Air-Powered Models Connect your gun with 1/8" NPT thread.



KIT 445-2 Regulator and Hose with Quick Disconnect Plug



KIT 272-3 Hose with Quick Disconnect Plug



KIT 363-1 Quick Disconnect Plug with 1/8" NPT Thread



KIT 137-5 Gun Regulator



KIT 445-1 Gun Regulator with Quick Disconnect Plug

* Guns are built to operate at a maximum air-pressure of 120psi. The maximum supply air-pressure into a regulator should not exceed 300psi.